Baysek EL-150

Automatic Feed Rotary Anvil - Flat Die Cutting

Fully Pneumatic Stripped Waste

EL150

Baysek

One Operator

The

- Friendly Touch Screen Controls
- No Make Ready Required
- Easy Set Up for Quick Order Changes
- Corrugated to Solid Board & Other Substrates
- Multiple Outs with No Nicks or Angel Hair
- Versatile Size Format
- Automatic Feed from 30" Pile
- Single to Multiple Bundle Count



See Our Machines in Action at www.baysek.com



Nick-Free, Multiple-Out EL-150 Die Cutter Specifications

_								Includes Preload and Out Feed Conveyor		
	Sheet Size	Maximum		Minimum		Floor	Through	9530 or 13208 mm	376 or 520 in.	
Г	Through	1220 to 2133 mm	48 to 84 in.	500 mm	20 in.		Across	2743 mm	108 in.	
	Across	1422 to 1320 mm	56 to 52 in.	500 mm	20 in.		Height	2235 mm	83 in.	
							Electric	380/480 Volts - 3 Phase - 50/60 Hz - 50/30 Amps		
	Pile Height	Pile Height762 mm30 in.					pressed Air	1.70m ³ /minute @ 6.9 Bar - 60ft ³ /minute @ 100PSI		
	Speed	1,000 to 650 sheets/hr.				Was	ste Removal	240 m ³ /minute - 8,500 ft. ³ /minute		

Upgrade your Baysek EL-150 for a Larger Baysek Die Cutter at any time *Dies are interchangeable on all Baysek die cutter models for ease of transfer and a quick return on investment



Changing the Industry's Perception One Machine at a Time...



P.O. Box 282, Amherst, WI 54406 Phone 715.824.5300 Email sales@baysek.com Website www.baysek.com